


## 45° NPT Elbow

**150# Malleable Iron**

Inches / Pounds



Part #	Size	A	Approximate Weight (in Lbs.)
K45E.125MI	1/8	0.60	0.07
K45E.25MI	1/4	0.73	0.11
K45E.375MI	3/8	0.80	0.15
K45E.5MI	1/2	0.88	0.22
K45E.75MI	3/4	0.98	0.34
K45E1MI	1	1.12	0.57
K45E1.25MI	1 1/4	1.29	0.84
K45E1.5MI	1 1/2	1.43	1.14
K45E2MI	2	1.68	1.70
K45E2.5MI	2 1/2	1.95	2.97
K45E3MI	3	2.17	4.65
K45E4MI	4	2.61	7.62
K45E5MI	5	3.05	12.10
K45E6MI	6	3.46	18.20
K45E8MI	8	4.00	26.10

***\*Malleable Castings conform to ASTM A197***

***\*Malleable Fitting Dimensions conform to ASME B16.3***

***\*Malleable Bushings, Plugs and Locknuts conform to ASME B16.14***

***\*Malleable Unions conform to ASME B16.39***

***\*NPT Threads on all fittings conform to ASME B1.20.1***

***\*Class 150 fittings are UL listed and FM approved at 300 psi***

***\*Class 300 fittings are UL listed***