


45° Elbows

STANDARD WEIGHT

Inches / Pounds



Part #	Nominal Pipe Size	Outside Diameter	Inside Diameter	Wall Thickness	Center to End (A)	Approximate Weight (in Lbs.)
K45E.5	1/2	0.84	0.622	0.109	0.62	0.09
K45E.75	3/4	1.05	0.824	0.113	0.75	0.10
K45E1	1	1.32	1.05	0.133	0.88	0.22
K45E1.25	1 1/4	1.66	1.38	0.140	1.00	0.33
K45E1.5	1 1/2	1.90	1.61	0.145	1.12	0.43
L45E2	2	2.38	2.07	0.154	1.38	0.85
K45E2.5	2 1/2	2.88	2.47	0.203	1.75	1.7
K45E3	3	3.50	3.07	0.216	2.00	2.5
K45E3.5	3 1/2	4.00	3.55	0.226	2.25	3.4
K45E4	4	4.50	4.03	0.237	2.50	4.5
K45E5	5	5.56	5.05	0.258	3.12	7.5
K45E6	6	6.62	6.06	0.280	3.75	11.7
K45E8	8	8.62	7.98	0.322	5.00	23.3
K45E10	10	10.75	10.02	0.365	6.25	40.9
K45E12	12	12.75	12.00	0.375	7.50	61.4
K45E14	14	14.00	13.25	0.375	8.75	78.1
K45E16	16	16.00	15.25	0.375	10.00	101
K45E18	18	18.00	17.25	0.375	11.25	128
K45E20	20	20.00	19.25	0.375	12.50	159
K45E22	22	22.00	21.25	0.375	13.50	192
K45E24	24	24.00	23.25	0.375	15.00	231
K45E26	26	26.00	25.25	0.375	16.00	299
K45E30	30	30.00	29.25	0.375	18.50	358
K45E34	34	34.00	33.25	0.375	21.00	463
K45E36	36	36.00	35.25	0.375	22.25	518
K45E42	42	42.00	41.25	0.375	26.00	707
K45E48	48	48.00	47.25	0.375	29.88	1,000

* Dimensions conform to ASME B16.9 & material conforms to ASTM SA-234 Grade B.