




Full Coupling - 150#
316 Stainless Steel
Inches / Pounds



Part #	Nominal Pipe Size	(A) Coupling Length	(B) Coupling Outside Diameter	Threads per Inch	Approximate Weight Each
KFC18SS	1/8	0.790	0.550	27	0.04
KFC14SS	1/4	1.060	0.730	18	0.07
KFC38SS	3/8	1.100	0.850	18	0.07
KFC12SS	1/2	1.400	1.050	14	0.16
KFC34SS	3/4	1.480	1.250	14	0.19
KFC1SS	1	1.690	1.560	11-1/2	0.37
KFC114SS	1 1/4	1.890	1.910	11-1/2	0.53
KFC112SS	1 1/2	1.890	2.170	11-1/2	0.65
KFC2SS	2	2.200	2.262	11-1/2	0.99
KFC212SS	2 1/2	2.560	3.330	8	2.07
KFC3SS	3	2.800	3.960	8	2.77
KFC4SS	4	3.270	5.100	8	5.11
KFC6SS	6	3.940	7.060	8	7.95

***316 Stainless Steel Couplings meet the following casting specifications: ASTM A351 ACI Grade CF8M (316)**

***NPT threads conform to ASME B1.20.1**

***Manufacturing facility is ISO 9001:2008 Certified**