




NPT Threaded Caps  
**300# Malleable Iron, Galvanized**  
 Inches / Pounds



Part #	Size	A	Approximate Weight (in Lbs)
KC.25MIG300	1/4	0.78	0.1
KC.375MIG300	3/8	0.83	0.1
KC.5MIG300	1/2	0.98	0.2
KC.75MIG300	3/4	1.08	0.3
KC1MIG300	1	1.26	0.5
KC1.25MIG300	1 1/4	1.38	0.8
KC1.5MIG300	1 1/2	1.43	1.1
KC2MIG300	2	1.68	1.7
KC2.5MIG300	2 1/2	2.06	2.8
KC3MIG300	3	2.17	4.2
KC4MIG300	4	2.48	7.2

***\*Malleable Castings conform to ASTM A197***

***\*Malleable Fitting Dimensions conform to ASME B16.3***

***\*NPT Threads on all fittings conform to ASME B1.20.1***

***\*Class 300 fittings are UL listed***

***\*Hot-dipped galvanized fittings conform to ASTM A153***

***\*Hot-dipped galvanized fittings are certified to NSF/ANSI 372 and California AB1953 Lead Free***

Pipe Fitting Direct  
 690 Craig Rd  
 Edgerton, WI 53534

Phone: (608) 371-9313

Email: sales@pipefittingdirect.com