




Reducing Couplings

304 Stainless Steel

Inches / Pounds




Part #	NPT Thread Sizes (inch)	Length (A)	Approx Weight (in Lbs.)
KRC.25X.125S	1/4 x 1/8	1.12	0.07
KRC.375X.125S	3/8 x 1/8	1.59	0.13
KRC.375X.25S	3/8 x 1/4	1.59	0.15
KRC.5X.125S	1/2 x 1/8	1.75	0.16
KRC.5X.25S	1/2 x 1/4	1.75	0.18
KRC.5X.375S	1/2 x 3/8	1.75	0.20
KRC.75X.125S	3/4 x 1/8	1.75	0.21
KRC.75X.25S	3/4 x 1/4	1.75	0.21
KRC.75X.375S	3/4 x 3/8	1.75	0.23
KRC.75X.5S	3/4 x 1/2	1.75	0.26
KRC1X.125S	1 x 1/8	1.97	0.35
KRC1X.25S	1 x 1/4	1.97	0.36
KRC1X.375S	1 x 3/8	1.97	0.37
KRC1X.5S	1 x 1/2	1.97	0.36
KRC1X.75S	1 x 3/4	1.97	0.42
KRC1.25X.25S	1-1/4 x 1/4	1.97	0.45
KRC1.25X.375S	1-1/4 x 3/8	1.97	0.51
KRC1.25X.5S	1-1/4 x 1/2	1.97	0.48
KRC1.25X.75S	1-1/4 x 3/4	1.97	0.53
KRC1.25X1S	1-1/4 x 1	1.97	0.62
KRC1.5X.125S	1-1/2 x 1/8	2.26	0.59
KRC1.5X.25S	1-1/2 x 1/4	2.26	0.59
KRC1.5X.375S	1-1/2 x 3/8	2.26	0.62
KRC1.5X.5S	1-1/2 x 1/2	2.26	0.61
KRC1.5X.75S	1-1/2 x 3/4	2.26	0.66
KRC1.5X1S	1-1/2 x 1	2.26	0.70
KRC1.5X1.25S	1-1/2 x 1-1/4	2.26	0.75
KRC2X.25S	2 x 1/4	2.64	0.93
KRC2X.375S	2 x 3/8	2.64	0.96
KRC2X.5S	2 x 1/2	2.64	0.98
KRC2X.75S	2 x 3/4	2.64	1.03
KRC2X1S	2 x 1	2.64	1.07
KRC2X1.25S	2 x 1-1/4	2.64	1.12
KRC2X1.5S	2 x 1 1/2	2.64	1.13

(CONTINUED ON NEXT PAGE)

Reducing Couplings

304 Stainless Steel

Inches / Pounds



Part #	NPT Thread Sizes (inch)	Length (A)	Approx Weight (in Lbs.)
KRC2.5X.5S	2-1/2 x 1/2	2.95	1.68
KRC2.5X.75S	2-1/2 x 3/4	2.95	1.60
KRC2.5X1S	2-1/2 x 1	2.95	1.68
KRC2.5X1.25S	2-1/2 x 1-1/4	2.95	1.73
KRC2.5X1.5S	2-1/2 x 1-1/2	2.95	1.78
KRC2.5X2S	2-1/2 x 2	2.95	1.92
KRC3X.75S	3 x 3/4	3.27	2.71
KRC3X1S	3 x 1	3.27	2.68
KRC3X1.25S	3 x 1-1/4	3.27	2.79
KRC3X1.5S	3 x 1-1/2	3.27	2.73
KRC3X2S	3 x 2	3.27	2.84
KRC3X2.5S	3 x 2-1/2	3.27	3.10
KRC4X1S	4 x 1	3.82	4.73
KRC4X1.5S	4 x 1-1/2	3.82	4.86
KRC4X2S	4 x 2	3.82	5.03
KRC4X2.5S	4 x 2-1/2	3.82	5.13
KRC4X3S	4 x 3	3.82	5.56

* Castings conform to ASTM A351 ACI Grade CF8

* Threading per ASME B1.20.1

* Manufactured in ISO 2001:2008 certified facility