




Reducing Couplings

Class 150, Malleable Iron

Inches / Pounds



Part #	NPT Thread Sizes (inch)	Length (A)	Approximate Weight (in Lbs.)
KRC.25X.125	1/4 x 1/8	1.00	0.1
KRC.375X.125	3/8 x 1/8	1.13	0.1
KRC.375X.25	3/8 x 1/4	1.13	0.1
KRC.5X.125	1/2 x 1/8	1.25	0.1
KRC.5X.25	1/2 x 1/4	1.25	0.1
KRC.5X.375	1/2 x 3/8	1.25	0.1
KRC.75X.125	3/4 x 1/8	1.44	0.2
KRC.75X.25	3/4 x 1/4	1.44	0.2
KRC.75X.375	3/4 x 3/8	1.44	0.2
KRC.75X.5	3/4 x 1/2	1.44	0.2
KRC1X.25	1 x 1/4	1.69	0.3
KRC1X.375	1 x 3/8	1.69	0.3
KRC1X.5	1 x 1/2	1.69	0.3
KRC1X.75	1 x 3/4	1.69	0.4
KRC1.25X.375	1-1/4 x 3/8	2.06	0.5
KRC.125X.5	1-1/4 x 1/2	2.06	0.5
KRC1.25X.75	1-1/4 x 3/4	2.06	0.5
KRC1.25X1	1-1/4 x 1	2.06	0.5
KRC1.5X.375	1-1/2 x 3/8	2.31	0.6
KRC1.5X.5	1-1/2 x 1/2	2.31	0.6
KRC1.5X.75	1-1/2 x 3/4	2.31	0.6
KRC1.5X1	1-1/2 x 1	2.31	0.7
KRC1.5X1.25	1-1/2 x 1-1/4	2.31	0.7
KRC2X.375	2 x 3/8	2.81	0.9
KRC2X.5	2 x 1/2	2.81	0.9
KRC2X.75	2 x 3/4	2.81	1.0
KRC2X1	2 x 1	2.81	1.0
KRC2X1.25	2 x 1-1/4	2.81	1.0
KRC2X1.5	2 x 1 1/2	2.81	1.0
KRC2.5X.75	2-1/2 x 3/4	3.25	1.5
KRC2.5X1	2-1/2 x 1	3.25	1.6
KRC2.5X1.25	2-1/2 x 1-1/4	3.25	1.7
KRC2.5X1.5	2-1/2 x 1-1/2	3.25	1.7
KRC2.5X2	2-1/2 x 2	3.25	1.8
KRC3X.75	3 x 3/4	3.69	2.4
KRC3X1	3 x 1	3.69	2.2
KRC3X1.25	3 x 1-1/4	3.69	2
KRC3X1.5	3 x 1-1/2	3.69	2.2
KRC3X2	3 x 2	3.69	2.4
KRC3X2.5	3 x 2-1/2	3.69	2.5


(continued on next page)



Reducing Couplings

Class 150, Malleable Iron

Inches / Pounds



Part #	NPT Thread Sizes (inch)	Length (A)	Approximate Weight (in Lbs.)
KRC4X1	4 x 1	4.38	3.7
KRC4X1.25	4 x 1-1/4	4.38	3.7
KRC4X1.5	4 x 1-1/2	4.38	4.4
KRC4X2	4 x 2	4.38	4.4
KRC4X2.5	4 x 2-1/2	4.38	4
KRC4X3	4 x 3	4.38	4
KRC5X4	5 x 4	4.86	9.8
KRC6X2	6 x 2	4.20	7.5
KRC6X3	6 x 3	4.20	7.9
KRC6X4	6 x 4	4.20	9.9
KRC6X5	6 x 5	4.20	8.7

* Castings conform to ASTM A197

* Dimensions conform to ASME 16.3

* Threading per ASME B1.20.1

* UL Listed and FM Approved at 300 PSI