




Threaded Reducing 90 deg Elbows

Class 150, Malleable Iron

Inches / Pounds



Part #	NPT Size (A)	NPT Size (B)	End to Center Length (A)	End to Center Length (B)	Approximate Weight (in Lbs.)
KR90E.25X.18	1/4	1/8	0.76	0.74	0.09
KR90E.38X.25	3/8	1/4	0.90	0.88	0.13
KR90E.5X.25	1/2	1/4	0.98	0.97	0.16
KR90E.5X.38	1/2	3/8	1.04	1.03	0.18
KR90E.75X.25	3/4	1/4	1.08	1.05	0.22
KR90E.75X.38	3/4	3/8	1.13	1.12	0.26
KR90E.75X.5	3/4	1/2	1.22	1.20	0.31
KR90E1X.25	1	1/4	1.22	1.10	0.32
KR90E1X.38	1	3/8	1.27	1.18	0.36
KR90E1X.5	1	1/2	1.36	1.26	0.41
KR90E1X.75	1	3/4	1.45	1.37	0.49
KR90E1.25X.5	1-1/4	1/2	1.53	1.34	0.56
KR90E1.25X.75	1-1/4	3/4	1.62	1.45	0.65
KR90E1.25X1	1-1/4	1	1.67	1.58	0.76
KR90E1.5X.5	1-1/2	1/2	1.75	1.52	0.66
KR90E1.5X.75	1-1/2	3/4	1.75	1.52	0.75
KR90E1.5X1	1-1/2	1	1.80	1.65	0.90
KR90E1.5X1.25	1-1/2	1-1/4	1.88	1.80	1.03
KR90E2X.5	2	1/2	1.97	1.60	0.95
KR90E2X.75	2	3/4	1.97	1.60	1.07
KR90E2X1	2	1	2.02	1.73	1.25
KR90E2X1.25	2	1-1/4	2.10	1.90	1.36
KR90E2X1.5	2	1-1/2	2.16	2.02	1.56
KR90E2.5X1.25	2-1/2	1-1/4	2.44	2.03	2.10
KR90E2.5X1.5	2-1/2	1-1/2	2.51	2.16	2.21
KR90E2.5X2	2-1/2	2	2.60	2.39	2.53
KR90E3X1	3	1	2.66	1.99	2.47
KR90E3X1.5	3	1-1/2	2.80	2.28	3.02
KR90E3X2	3	2	2.89	2.52	3.45
KR90E3X2.5	3	2-1/2	2.99	2.83	4.12
KR90E4X2	4	2	3.41	2.74	5.03
KR90E4X2.5	4	2-1/2	3.50	3.05	5.80
KR90E4X3	4	3	3.60	3.30	6.66

* Castings conform to ASTM A197

* Dimensions conform to ASME 16.3

* Threading per ASME B1.20.1

* UL Listed and FM Approved at 300 PSI