




Threaded Reducing 90 deg Elbows

Class 150, Galvanized Malleable Iron

Inches / Pounds



Part #	NPT Size (A)	NPT Size (B)	End to Center Length (A)	End to Center Length (B)	Approximate Weight (in Lbs.)
KR90E.25X.18G	1/4	1/8	0.76	0.74	0.09
KR90E.38X.25G	3/8	1/4	0.90	0.88	0.13
KR90E.5X.25G	1/2	1/4	0.98	0.97	0.16
KR90E.5X.38G	1/2	3/8	1.04	1.03	0.18
KR90E.75X.25G	3/4	1/4	1.08	1.05	0.22
KR90E.75X.38G	3/4	3/8	1.13	1.12	0.26
KR90E.75X.5G	3/4	1/2	1.22	1.20	0.31
KR90E1X.25G	1	1/4	1.22	1.10	0.32
KR90E1X.38G	1	3/8	1.27	1.18	0.36
KR90E1X.5G	1	1/2	1.36	1.26	0.41
KR90E1X.75G	1	3/4	1.45	1.37	0.49
KR90E1.25X.5G	1-1/4	1/2	1.53	1.34	0.56
KR90E1.25X.75G	1-1/4	3/4	1.62	1.45	0.65
KR90E1.25X1G	1-1/4	1	1.67	1.58	0.76
KR90E1.5X.5G	1-1/2	1/2	1.75	1.52	0.66
KR90E1.5X.75G	1-1/2	3/4	1.75	1.52	0.75
KR90E1.5X1G	1-1/2	1	1.80	1.65	0.90
KR90E1.5X1.25G	1-1/2	1-1/4	1.88	1.80	1.03
KR90E2X.5G	2	1/2	1.97	1.60	0.95
KR90E2X.75G	2	3/4	1.97	1.60	1.07
KR90E2X1G	2	1	2.02	1.73	1.25
KR90E2X1.25G	2	1-1/4	2.10	1.90	1.36
KR90E2X1.5G	2	1-1/2	2.16	2.02	1.56
KR90E2.5X1.5G	2-1/2	1-1/2	2.51	2.16	2.21
KR90E2.5X2G	2-1/2	2	2.60	2.39	2.53
KR90E3X1G	3	1	2.66	1.99	2.47
KR90E3X1.5G	3	1-1/2	2.80	2.28	3.02
KR90E3X2G	3	2	2.89	2.52	3.45
KR90E3X2.5G	3	2-1/2	2.99	2.83	4.12
KR90E4X1.5G	4	1-1/2	2.31	2.50	4.54
KR90E4X2G	4	2	3.41	2.74	5.03
KR90E4X2.5G	4	2-1/2	3.50	3.05	5.80
KR90E4X3G	4	3	3.60	3.30	6.66

* Castings conform to ASTM A197

* Hot-dipped galvanized to ASTM A153

* Dimensions conform to ASME 16.3

* Threading per ASME B1.20.1

* UL Listed and FM Approved at 300 PSI