


Bull Head Tee

150#, Galvanized MI

Inches / Pounds



**Approximate
Weight
(in LBS)**

Part #	Lateral Sizes (NPT)	Head Size (NPT)	Lateral Center to End (A)	Lateral End to Center (B)	Bull End to Center (C)	Approximate Weight (in LBS)
KBT.5X.75MIG	1/2	3/4	1.22	1.22	1.20	0.3
KBT.5X1MIG	1/2	1	1.36	1.36	1.26	0.5
KBT.75X1MIG	3/4	1	1.45	1.45	1.37	0.5
KBT.75X1.25MIG	3/4	1-1/4	1.62	1.62	1.45	0.7
KBT1X1.25MIG	1	1-1/4	1.67	1.67	1.58	0.9
KBT1X1.5MIG	1	1-1/2	1.80	1.80	1.65	1.1
KBT1X2MIG	1	2	2.02	2.02	1.73	1.2
KBT1.25X1.5MIG	1-1/4	1-1/2	1.88	1.88	1.82	1.3
KBT1.25X2MIG	1-1/4	2	2.10	2.10	1.90	1.8
KBT1.5X2MIG	1-1/2	2	2.16	2.16	2.02	1.7
KBT2X2.5MIG	2	2	2.60	2.60	2.39	3.0
KBT2.5X3MIG	2-1/2	3	3.00	3.00	2.83	5.8

****Material conforms to ASTM A197***

****Dimensions conform to ASME B16.3***

****NPT Threads on all fittings conform to ASME B1.20.1***

****Hot-dipped galvanized fittings conform to ASTM A153***

****Hot-dipped galvanized fittings are certified to; NSF/ANSI 372 and California AB1953 Lead Free***