




Blind Plate Flanges

Class 150 spaced, 316 SS
Inches / Pounds



Part #	NPS Size	Outside Diameter (O.D.)	Bolt Hole Center Diameter (B.H.C.)	Bolt Hole Diameter (B.H.)	Flange Thickness (THK)	Number of Bolt Holes	Est Weight
PFDAB1PSS	1	4.25	3.12	0.625	0.5	4	1.9
PFDAB1.5PSS	1-1/2	5.0	3.88	0.625	0.5	4	2.7
PFDAB2PSS	2	6.0	4.75	0.75	0.5	4	3.9
PFDAB2.5PSS	2.5	7.0	5.50	0.75	0.5	4	5.5
PFDAB3PSS	3	7.5	6.00	0.75	0.5	4	6.3
PFDAB4PSS	4	9.0	7.50	0.75	0.5	8	9
PFDAB5PSS	5	10.0	8.50	0.88	0.5	8	10
PFDAB6PSS	6	11.0	9.50	0.88	0.5	8	13.5
PFDAB8PSS	8	13.5	11.75	0.88	0.5	8	20.8
PFDAB10PSS	10	16.0	14.25	1	0.625	12	28.5
PFDAB12PSS	12	19.0	17	1	0.625	12	40.7

* Constructed of ASTM A240 316 stainless plate steel or cast in conformance with ASTM A351

* Spacing per ASME B16.5 Class 150, **except for thickness**