


# Threaded 45° Elbow

## 125# Bronze

### Inches / Pounds



| Part #    | Size  | A     | Approximate Weight (in Lbs.) |
|-----------|-------|-------|------------------------------|
| K45E.125B | 1/8   | 42.00 | 0.1                          |
| K45E.25B  | 1/4   | 0.56  | 0.1                          |
| K45E.375B | 3/8   | 0.63  | 0.2                          |
| K45E.5B   | 1/2   | 0.78  | 0.2                          |
| K45E.75B  | 3/4   | 0.89  | 0.3                          |
| K45E1B    | 1     | 1.06  | 0.5                          |
| K45E1.25B | 1 1/4 | 1.22  | 0.8                          |
| K45E1.5B  | 1 1/2 | 1.30  | 1.1                          |
| K45E2B    | 2     | 1.45  | 1.7                          |
| K45E2.5B  | 2 1/2 | 1.95  | 3.2                          |
| K45E3B    | 3     | 2.17  | 4.8                          |
| K45E4B    | 4     | 2.61  | 8.2                          |

***\*Bronze castings conform to ASTM B62, UNS Alloy C83600***

***\*Dimensions conform to ASME B16.5***

***\*NPT Threads on all fittings conform to ASME B1.20.1***

***\*Fittings conform to AWWA C800***