




Threaded Reducing 90 deg Elbows

Class 125, Bronze

Inches / Pounds



Part #	NPT Size (A)	NPT Size (B)	End to Center Length (A)	End to Center Length (B)	Approximate Weight (in Lbs.)
KR90E.38X.25B	3/8	1/4	0.78	0.75	0.2
KR90E.5X.25B	1/2	1/4	0.98	0.97	0.2
KR90E.5X.38B	1/2	3/8	0.93	0.90	0.2
KR90E.75X.25B	3/4	1/4	1.08	1.05	0.3
KR90E.75X.38B	3/4	3/8	1.13	1.12	0.3
KR90E.75X.5B	3/4	1/2	1.11	1.08	0.4
KR90E1X.5B	1	1/2	1.24	1.20	0.5
KR90E1X.75B	1	3/4	1.31	1.30	0.6
KR90E1.25X.5B	1-1/4	1/2	1.53	1.34	0.7
KR90E1.25X.75B	1-1/4	3/4	1.48	1.39	0.8
KR90E1.25X1B	1-1/4	1	1.60	1.52	0.8
KR90E1.5X.5B	1-1/2	1/2	1.62	1.38	0.7
KR90E1.5X.75B	1-1/2	3/4	1.72	1.52	0.9
KR90E1.5X1B	1-1/2	1	1.72	1.55	1.1
KR90E1.5X1.25B	1-1/2	1-1/4	1.81	1.72	1.1
KR90E2X.5B	2	1/2	1.90	1.56	1.1
KR90E2X.75B	2	3/4	1.90	1.68	1.2
KR90E2X1B	2	1	2.02	1.73	1.4
KR90E2X1.25B	2	1-1/4	2.10	1.90	1.5
KR90E2X1.5B	2	1-1/2	2.07	1.89	1.7
KR90E2.5X1.5B	2-1/2	1-1/2	2.51	2.16	3.0
KR90E2.5X2B	2-1/2	2	2.60	2.39	3.2
KR90E3X2B	3	2	2.89	2.52	4.2
KR90E3X2.5B	3	2-1/2	2.99	2.83	4.1

*Bronze castings conform to ASTM B62, UNS Alloy C83600

*Dimensions conform to ASME B16.5

*NPT Threads on all fittings conform to ASME B1.20.1

*Fittings conform to AWWA C800