



Threaded Reducing 90 deg Elbows

Class 125, Lead Free Bronze

Inches / Pounds



Part #	NPT Size (A)	NPT Size (B)	End to Center Length (A)	End to Center Length (B)	Approximate Weight (in Lbs.)
KR90E.5X.25LB	1/2	1/4	0.98	0.97	0.2
KR90E.5X.38LB	1/2	3/8	0.93	0.90	0.2
KR90E.75X.5LB	3/4	1/2	1.11	1.08	0.4
KR90E1X.5LB	1	1/2	1.24	1.20	0.5
KR90E1X.75LB	1	3/4	1.31	1.30	0.5
KR90E1.25X.75LB	1-1/4	3/4	1.48	1.39	0.7
KR90E1.25X1LB	1-1/4	1	1.60	1.52	0.7
KR90E1.5X1LB	1-1/2	1	1.72	1.55	1.0
KR90E1.5X1.25LB	1-1/2	1-1/4	1.81	1.72	1.0
KR90E2X1LB	2	1	2.02	1.73	1.4
KR90E2X1.25LB	2	1-1/4	2.10	1.90	1.5
KR90E2X1.5LB	2	1-1/2	2.07	1.89	1.6
KR90E2.5X2LB	2-1/2	2	2.60	2.39	3.1
KR90E3X2.5LB	3	2-1/2	2.99	2.83	4.0

*Lead Free Bronze castings conform to ASTM B584, UNS Alloy C89833

*Dimensions conform to ASME B16.15

*NPT Threads on all fittings conform to ASME B1.20.1

*Fittings conform to AWWA C800

*Certified to ANSI/NSF 372, SWDA and California AB 1953

