


NPT Hex Reducing Bushings

125#, Bronze

Inches / Pounds




Part #	Size	A (height)	B (hex head width)	Approximate Weight (in LBS)	Hex
KHB.25X.125B	1/4 x 1/8	0.65	0.66	0.02	Out
KHB.375X.125B	3/8 x 1/8	0.70	0.70	0.06	Out
KHB.375X.25B	3/8 x 1/4	0.70	0.73	0.04	Out
KHB.5X.125B	1/2 x 1/8	0.81	0.90	0.10	Out
KHB.5X.25B	1/2 x 1/4	0.81	0.90	0.09	Out
KHB.5X.375B	1/2 x 3/8	0.81	0.90	0.08	Out
KHB.75X.125B	3/4 x 1/8	0.88	1.18	0.17	Out
KHB.75X.25B	3/4 x 1/4	0.93	1.18	0.15	Out
KHB.75X.375B	3/4 x 3/8	0.93	1.18	0.14	Out
KHB.75X.5B	3/4 x 1/2	0.93	1.18	0.14	Out
KHB1X.25B	1 x 1/4	1.13	1.12	0.23	In
KHB1X.375B	1 x 3/8	1.13	1.12	0.22	In
KHB1X.5B	1 x 1/2	1.10	1.44	0.25	Out
KHB1X.75B	1 x 3/4	1.10	1.44	0.21	Out
KHB1.25X.5B	1 1/4 x 1/2	1.18	1.80	0.34	In
KHB1.25X.75B	1 1/4 x 3/4	1.18	1.80	0.40	Out
KHB1.25X1B	1 1/4 x 1	1.18	1.80	0.33	Out
KHB1.5X.25B	1 1/2 x 1/4	1.27	1.15	0.47	In
KHB1.5X.375B	1 1/2 x 3/8	1.30	1.34	0.45	Out
KHB1.5X.5B	1 1/2 x 1/2	1.27	1.34	0.44	In
KHB1.5X.75B	1 1/2 x 3/4	1.27	1.63	0.48	In
KHB1.5X1B	1 1/2 x 1	1.19	2.04	0.53	Out
KHB1.5X1.25B	1 1/2 x 1 1/4	1.19	2.04	0.45	Out
KHB2X.5B	2 x 1/2	1.35	1.36	0.67	In
KHB2X.75B	2 x 3/4	1.35	1.65	0.74	In
KHB2X1B	2 x 1	1.35	2.00	0.76	Out
KHB2X1.25B	2 x 1 1/4	1.35	2.50	0.86	Out
KHB2X1.5B	2 x 1 1/2	1.35	2.55	0.83	Out

(Continued on next page)

NPT Hex Reducing Bushings

125#, Bronze

Inches / Pounds



Part #	Size	A (height)	B (hex head width)	Approximate Weight (in LBS)	Hex
KHB2.5X.5B	2½ x ½	1.64	3.15	1.3	Out
KHB2.5X.75B	2½ x ¾	1.58	1.65	1.1	In
KHB2.5X1B	2½ x 1	1.58	2.00	1.2	In
KHB2.5X1.25B	2½ x 1¼	1.60	2.39	1.2	In
KHB2.5X1.5B	2½ x 1½	1.52	2.70	1.4	In
KHB2.5X2B	2½ x 2	1.62	3.15	1.1	Out
KHB3X.5B	3 x ½	1.60	1.35	1.9	In
KHB3X.75B	3 x ¾	1.70	1.65	1.9	In
KHB3X1.5B	3 x 1	1.60	2.00	1.7	In
KHB3X1.25B	3 x 1¼	1.70	2.40	1.8	In
KHB3X1.5B	3 x 1½	1.70	2.70	1.8	In
KHB3X2B	3 x 2	1.70	3.55	2.3	Out
KHB3X2.5B	3 x 2½	1.70	3.90	2.2	Out
KHB4X1.5B	4 x 1½	1.80	2.70	3.4	In
KHB4X2B	4 x 2	1.80	3.30	3.6	In
KHB4X2.5B	4 x 2½	2.10	4.75	3.9	Out
KHB4X3B	4 x 3	2.10	4.75	4.2	Out

***Bronze castings conform to ASTM B62, UNS Alloy C83600**

***Dimensions conform to ASME B16.5**

***NPT Threads on all fittings conform to ASME B1.20.1**

***Fittings conform to AWWA C800**