


NPT Reducing Couplings

Class 125, Bronze

Inches / Pounds



Part #	NPT Thread Sizes (inch)	Length (A)	Approximate Weight (in Lbs.)
KRC.25X.125B	1/4 x 1/8	0.88	0.1
KRC.375X.125B	3/8 x 1/8	0.92	0.1
KRC.375X.25B	3/8 x 1/4	1.01	0.1
KRC.5X.125B	1/2 x 1/8	1.13	0.2
KRC.5X.25B	1/2 x 1/4	1.13	0.2
KRC.5X.375B	1/2 x 3/8	1.17	0.2
KRC.75X.125B	3/4 x 1/8	1.24	0.1
KRC.75X.25B	3/4 x 1/4	1.24	0.2
KRC.75X.375B	3/4 x 3/8	1.24	0.2
KRC.75X.5B	3/4 x 1/2	1.36	0.2
KRC1X.25B	1 x 1/4	1.49	0.4
KRC1X.375B	1 x 3/8	1.49	0.4
KRC1X.5B	1 x 1/2	1.49	0.3
KRC1X.75B	1 x 3/4	1.56	0.4
KRC.125X.5B	1-1/4 x 1/2	1.65	0.6
KRC1.25X.75B	1-1/4 x 3/4	1.65	0.6
KRC1.25X1B	1-1/4 x 1	1.77	0.5
KRC1.5X.5B	1-1/2 x 1/2	1.80	0.8
KRC1.5X.75B	1-1/2 x 3/4	1.80	0.8
KRC1.5X1B	1-1/2 x 1	1.89	0.7
KRC1.5X1.25B	1-1/2 x 1-1/4	2.03	1.0
KRC2X.5B	2 x 1/2	2.03	1.3
KRC2X.75B	2 x 3/4	2.03	1.3
KRC2X1B	2 x 1	2.03	1.0
KRC2X1.25B	2 x 1-1/4	2.06	1.4
KRC2X1.5B	2 x 1 1/2	3.25	1.1
KRC2.5X1B	2-1/2 x 1	3.25	2.0
KRC2.5X1.25B	2-1/2 x 1-1/4	3.25	2.3
KRC2.5X1.5B	2-1/2 x 1-1/2	3.25	2.3
KRC2.5X2B	2-1/2 x 2	3.69	2.5
KRC3X1B	3 x 1	3.69	1.0
KRC3X1.25B	3 x 1-1/4	3.69	1.0
KRC3X1.5B	3 x 1-1/2	3.69	2.4
KRC3X2B	3 x 2	3.69	3.6
KRC3X2.5B	3 x 2-1/2	3.69	3.9
KRC4X2B	4 x 2	4.38	6.1
KRC4X2.5B	4 x 2-1/2	4.38	5.9
KRC4X3B	4 x 3	4.38	6.6

***Bronze castings conform to ASTM B62, UNS Alloy C83600**

***Dimensions conform to ASME B16.5**

***NPT Threads on all fittings conform to ASME B1.20.1**

***Fittings conform to AWWA C800**