




Socket Weld, Reducing Couplings

Class 3000, Forged 304 Stainless Steel

Inches / Pounds



Part #	NPS Sizes (inch)	Length (A)	Outside Diameter (B)	Approximate Weight (in Lbs.)
K3SWRC.5X.125S	1/2 x 1/8	1.14	1.27	0.2
K3SWRC.5X.25S	1/2 x 1/4	1.14	1.27	0.2
K3SWRC.5X.375S	1/2 x 3/8	1.14	1.27	0.2
K3SWRC.75X.25S	3/4 x 1/4	1.38	1.5	0.4
K3SWRC.75X.375S	3/4 x 3/8	1.38	1.5	0.4
K3SWRC.75X.5S	3/4 x 1/2	1.38	1.5	0.4
K3SWRC1X.25S	1 x 1/4	1.50	1.8	0.5
K3SWRC1X.375S	1 x 3/8	1.50	1.8	0.5
K3SWRC1X.5S	1 x 1/2	1.50	1.8	0.5
K3SWRC1X.75S	1 x 3/4	1.50	1.8	0.5
K3SWRC1.25X.5S	1-1/4 x 1/2	1.50	2.23	1.0
K3SWRC1.25X.75S	1-1/4 x 3/4	1.50	2.23	1.1
K3SWRC1.25X1S	1-1/4 x 1	1.50	2.23	1.0
K3SWRC1.5X.375S	1-1/2 x 3/8	1.50	2.55	1.3
K3SWRC1.5X.5S	1-1/2 x 1/2	1.50	2.55	1.3
K3SWRC1.5X.75S	1-1/2 x 3/4	1.50	2.55	1.3
K3SWRC1.5X1S	1-1/2 x 1	1.50	2.55	1.3
K3SWRC1.5X1.25S	1-1/2 x 1-1/4	1.50	2.55	1.3
K3SWRC2X.5S	2 x 1/2	2.00	2.96	2.6
K3SWRC2X.75S	2 x 3/4	2.00	2.96	2.3
K3SWRC2X1S	2 x 1	2.00	2.96	2.1
K3SWRC2X1.25S	2 x 1-1/4	2.00	2.96	2.1
K3SWRC2X1.5S	2 x 1 1/2	2.00	2.96	2.6
K3SWRC3X1.5S	3 x 1-1/2	2.00	4.27	4.1
K3SWRC3X2S	3 x 2	2.00	4.27	4.1

* Material conforms to ASME A182

* Dimensions conform to ASME 16.11