




Socket Weld, Reducing Couplings

Class 3000, Forged Carbon Steel

Inches / Pounds



Part #	NPS Sizes (inch)	Length (A)	Outside Diameter (B)	Approximate Weight (in Lbs.)
K3SWRC.5X.25	1/2 x 1/4	1.14	1.27	0.2
K3SWRC.5X.375	1/2 x 3/8	1.14	1.27	0.2
K3SWRC.75X.125	3/4 x 1/8	1.38	1.5	0.4
K3SWRC.75X.25	3/4 x 1/4	1.38	1.5	0.4
K3SWRC.75X.375	3/4 x 3/8	1.38	1.5	0.4
K3SWRC.75X.5	3/4 x 1/2	1.38	1.5	0.4
K3SWRC1X.25	1 x 1/4	1.50	1.8	0.5
K3SWRC1X.375	1 x 3/8	1.50	1.8	0.5
K3SWRC1X.5	1 x 1/2	1.50	1.8	0.5
K3SWRC1X.75	1 x 3/4	1.50	1.8	0.5
K3SWRC1.25X.5	1-1/4 x 1/2	1.50	2.23	1.0
K3SWRC1.25X.75	1-1/4 x 3/4	1.50	2.23	1.1
K3SWRC1.25X1	1-1/4 x 1	1.50	2.23	1.0
K3SWRC1.5X.375	1-1/2 x 3/8	1.50	2.55	2.0
K3SWRC1.5X.5	1-1/2 x 1/2	1.50	2.55	1.3
K3SWRC1.5X.75	1-1/2 x 3/4	1.50	2.55	1.3
K3SWRC1.5X1	1-1/2 x 1	1.50	2.55	1.6
K3SWRC1.5X1.25	1-1/2 x 1-1/4	1.50	2.55	1.3
K3SWRC2X.5	2 x 1/2	2.00	2.96	2.6
K3SWRC2X.75	2 x 3/4	2.00	2.96	2.3
K3SWRC2X1	2 x 1	2.00	2.96	2.1
K3SWRC2X1.25	2 x 1-1/4	2.00	2.96	2.1
K3SWRC2X1.5	2 x 1 1/2	2.00	2.96	2.6
K3SWRC2.5X.5	2-1/2 x 1/2	2.00	3.64	4.2
K3SWRC2.5X1	2-1/2 x 1	2.00	3.64	3.1
K3SWRC2.5X1.25	2-1/2 x 1-1/4	2.00	3.64	3.1
K3SWRC2.5X1.5	2-1/2 x 1-1/2	2.00	3.64	3.1
K3SWRC2.5X2	2-1/2 x 2	2.00	3.64	3.1
K3SWRC3X1	3 x 1	2.00	4.27	4.1
K3SWRC3X1.25	3 x 1-1/4	2.00	4.27	4.4
K3SWRC3X1.5	3 x 1-1/2	2.00	4.27	4.1
K3SWRC3X2	3 x 2	2.00	4.27	4.1
K3SWRC3X2.5	3 x 2-1/2	2.00	4.27	4.1
K3SWRC4X1.5	4 x 1-1/2	2.25	5.4	6
K3SWRC4X2	4 x 2	2.25	5.4	5.9
K3SWRC4X2.5	4 x 2-1/2	2.25	5.4	5.8
K3SWRC4X3	4 x 3	2.25	5.4	5.7

* Material conforms to ASTM A105N, Normalized

* Dimensions conform to ASME 16.11