


Weld on Long Radius 180 deg Return Bends

40/STD Schedule, Carbon Steel

Inches / Pounds



Part #	Nominal Pipe Size	Outside Diameter	Inside Diameter	Wall Thickness	Center to Center (O)	Back to Face (K)	Pipe Schedule	Approximate Weight (in Lbs.)
KLRB.5	1/2	0.84	0.622	0.109	3.00	1.88	40	0.32
KLRB.75	3/4	1.05	0.824	0.113	2.25	1.69	40	0.34
KLRB1	1	1.32	1.049	0.133	3.00	2.19	40	0.74
KLRB1.25	1 1/4	1.66	1.380	0.140	3.75	2.75	40	1.10
KLRB1.5	1 1/2	1.90	1.610	0.145	4.50	3.25	40	1.6
KLRB2	2	2.38	2.067	0.154	6.00	4.19	40	3.2
KLRB2.5	2 1/2	2.88	2.469	0.203	7.50	5.19	40	6.1
KLRB3	3	3.50	3.068	0.216	9.00	6.25	40	9.4
KLRB4	4	4.50	4.026	0.237	12.00	8.25	40	17.5
KLRB5	5	5.56	5.047	0.258	15.00	10.31	40	29.3
KLRB6	6	6.63	6.065	0.280	18.00	12.31	40	47
KLRB8	8	8.63	7.981	0.322	24.00	16.31	40	87
KLRB10	10	10.75	10.020	0.365	30.00	20.38	40	164
KLRB12	12	12.75	12.000	0.375	36.00	24.38	STD	237
KLRB14	14	14.00	13.625	0.375	42.00	28.00	STD	311
KLRB16	16	16.00	15.625	0.375	48.00	32.00	STD	408
KLRB18	18	18.00	17.625	0.375	54.00	36.00	STD	514
KLRB20	20	20.00	19.625	0.375	60.00	40.00	STD	636
KLRB22	22	22.00	21.625	0.375	66.00	44.00	STD	771
KLRB24	24	24.00	23.625	0.375	72.00	48.00	STD	908
KLRB26	26	26.00	25.625	0.375	78.00	52.00	STD	1191
KLRB30	30	30.00	29.625	0.375	90.00	60.00	STD	1541

* Dimensions conform to ASME B16.9 & material conforms to ASTM SA-234 Grade B