


Weld on Short Radius 180 deg Return Bends

40/STD Schedule, Carbon Steel

Inches / Pounds



Part #	Nominal Pipe Size	Outside Diameter	Inside Diameter	Wall Thickness	Center to Center (O)	Back to Face (K)	Pipe Schedule	Approximate Weight (in Lbs.)
KSRB1	1	1.32	1.049	0.133	2.00	1.62	40	0.50
KSRB1.25	1 1/4	1.66	1.380	0.140	2.50	2.06	40	0.80
KSRB1.5	1 1/2	1.90	1.610	0.145	3.00	2.44	40	1.1
KSRB2	2	2.38	2.067	0.154	4.00	3.19	40	1.9
KSRB2.5	2 1/2	2.88	2.469	0.203	5.00	3.94	40	4.0
KSRB3	3	3.50	3.068	0.216	6.00	4.75	40	6.0
KSRB4	4	4.50	4.026	0.237	8.00	6.25	40	12.2
KSRB5	5	5.56	5.047	0.258	10.00	7.75	40	19.2
KSRB6	6	6.63	6.065	0.280	12.00	9.31	40	33
KSRB8	8	8.63	7.981	0.322	16.00	12.31	40	65
KSRB10	10	10.75	10.020	0.365	20.00	15.38	40	112
KSRB12	12	12.75	12.000	0.375	24.00	18.38	STD	157
KSRB14	14	14.00	13.625	0.375	28.00	21.00	STD	208
KSRB16	16	16.00	15.625	0.375	32.00	24.00	STD	257
KSRB18	18	18.00	17.625	0.375	36.00	27.00	STD	325
KSRB20	20	20.00	19.625	0.375	40.00	30.00	STD	416
KSRB24	24	24.00	23.625	0.375	48.00	36.00	STD	592
KSRB26	26	26.00	25.625	0.375	60.00	45.00	STD	956
KSRB30	30	30.00	29.625	0.375	72.00	54.00	STD	1387

** Dimensions conform to ASME B16.9 & material conforms to ASTM SA-234 Grade B*