




Weld on Reducing Tees

Schedule 80/XS, Carbon Steel

Inches / Pounds



Part #	Dimensions of Run						Dimensions of Branch						Approx. Weight (in Lbs.)
	Nominal Pipe Size	Outside Diameter	Inside Diameter	Pipe Schedule	Wall Thickness	Center to Center (C)	Nominal Pipe Size	Outside Diameter	Inside Diameter	Pipe Schedule	Wall Thickness	Center to End (M)	
KRTXH.75X.5	¾	1.05	0.742	80	0.154	1.12	½	0.840	0.546	80	0.147	1.12	0.5
KRTXH1X.5	1	1.32	0.962	80	0.179	1.50	½	0.840	0.546	80	0.147	1.50	0.9
KRTXH1X.75	1	1.32	0.962	80	0.179	1.50	¾	1.050	0.742	80	0.154	1.50	1.0
KRTXH1.25X.5	1 ¼	1.66	1.278	80	0.191	1.88	½	0.840	0.546	80	0.147	1.88	1.6
KRTXH1.25X.75	1 ¼	1.66	1.278	80	0.191	1.88	¾	1.320	1.012	80	0.154	1.88	1.6
KRTXH1.25X1	1 ¼	1.66	1.278	80	0.191	1.88	1	1.050	0.692	80	0.179	1.88	1.6
KRTXH1.5X.5	1 ½	1.90	1.500	80	0.200	2.25	½	0.840	0.546	80	0.147	2.25	2.2
KRTXH1.5X.75	1 ½	1.90	1.500	80	0.200	2.25	¾	1.050	0.742	80	0.154	2.25	2.2
KRTXH1.5X1	1 ½	1.90	1.500	80	0.200	2.25	1	1.320	0.962	80	0.179	2.25	2.3
KRTXH1.5X1.25	1 ½	1.90	1.500	80	0.200	2.25	1 ¼	1.660	1.278	80	0.191	2.25	2.4
KRTXH2X.75	2	2.38	1.944	80	0.218	2.50	¾	1.050	0.742	80	0.154	1.75	3.5
KRTXH2X1	2	2.38	1.944	80	0.218	2.50	1	1.320	0.962	80	0.179	2.00	3.5
KRTXH2X1.25	2	2.38	1.944	80	0.218	2.50	1 ¼	1.66	1.278	80	0.191	2.25	3.7
KRTXH2X1.5	2	2.38	1.944	80	0.218	2.50	1 ½	1.90	1.500	80	0.200	2.38	3.8
KRTXH2.5X1	2 ½	2.88	2.328	80	0.276	3.00	1	1.32	0.962	80	0.179	2.25	5.8
KRTXH2.5X1.25	2 ½	2.88	2.328	80	0.276	3.00	1 ¼	1.66	1.278	80	0.191	2.5	6.0
KRTXH2.5X1.5	2 ½	2.88	2.328	80	0.276	3.00	1 ½	1.9	1.500	80	0.2	2.62	6.2
KRTXH2.5X2	2 ½	2.88	2.328	80	0.276	3.00	2	2.38	1.944	80	0.218	2.75	6.3

** Dimensions conform to ASME B16.9 & material conforms to ASTM SA-234 Grade B*

*****CONTINUED ON NEXT PAGE*****

Pipe Fittings Direct
690 Craig Rd
Edgerton, WI 53534
Phone: (608) 371-9313
Email: sales@pipefittingsdirect.com



Part #	Dimensions of Run						Dimensions of Branch						Approx. Weight (in Lbs.)
	Nominal Pipe Size	Outside Diameter	Inside Diameter	Pipe Schedule	Wall Thickness	Center to End (C)	Nominal Pipe Size	Outside Diameter	Inside Diameter	Pipe Schedule	Wall Thickness	Center to End (M)	
KRTXH3X1	3	3.50	2.900	80	0.3	3.38	1	1.32	0.962	80	0.179	2.62	7.8
KRTXH3X1.25	3	3.50	2.900	80	0.3	3.38	1 1/4	1.66	1.278	80	0.191	2.75	8.0
KRTXH3X1.5	3	3.50	2.900	80	0.3	3.38	1 1/2	1.9	1.500	80	0.2	2.88	8.1
KRTXH3X2	3	3.50	2.900	80	0.3	3.38	2	2.38	1.944	80	0.218	3	8.6
KRTXH3X2.5	3	3.50	2.900	80	0.3	3.38	2 1/2	2.88	2.328	80	0.276	3.25	8.8
KRTXH4X1.5	4	4.50	3.826	80	0.337	4.12	1 1/2	1.9	1.500	80	0.2	3.38	15.0
KRTXH4X2	4	4.50	3.826	80	0.337	4.12	2	2.38	1.944	80	0.218	3.5	15.1
KRTXH4X2.5	4	4.50	3.826	80	0.337	4.12	2 1/2	2.88	2.328	80	0.276	3.75	15.1
KRTXH4X3	4	4.50	3.826	80	0.337	4.12	3	3.5	2.900	80	0.3	3.88	15.4
KRTXH5X2	5	5.56	4.810	80	0.375	4.88	2	2.38	1.944	80	0.218	4.12	23.6
KRTXH5X2.5	5	5.56	4.810	80	0.375	4.88	2 1/2	2.88	2.328	80	0.276	4.25	23.9
KRTXH5X3	5	5.56	4.810	80	0.375	4.88	3	3.5	2.900	80	0.3	4.38	24.2
KRTXH5X4	5	5.56	4.810	80	0.375	4.88	4	4.5	3.826	80	0.337	4.62	25.4
KRTXH6X2	6	6.62	5.756	80	0.432	5.62	2	2.38	1.944	80	0.218	4.75	37.4
KRTXH6X2.5	6	6.62	5.756	80	0.432	5.62	2 1/2	2.88	2.328	80	0.276	4.75	38.2
KRTXH6X3	6	6.62	5.756	80	0.432	5.62	3	3.5	2.900	80	0.3	4.88	38.6
KRTXH6X4	6	6.62	5.756	80	0.432	5.62	4	4.5	3.826	80	0.337	5.12	39.3
KRTXH6X5	6	6.62	5.756	80	0.432	5.62	5	5.56	4.810	80	0.375	5.38	39.5
KRTXH8X3	8	8.62	7.620	80	0.5	7.00	3	3.5	2.900	80	0.3	6	68.3
KRTXH8X4	8	8.62	7.620	80	0.5	7.00	4	4.5	3.826	80	0.337	6.12	69.2
KRTXH8X5	8	8.62	7.620	80	0.5	7.00	5	5.56	4.810	80	0.375	6.38	69.4
KRTXH8X6	8	8.62	7.620	80	0.5	7.00	6	6.62	5.756	80	0.432	6.62	70.2
KRTXH10X4	10	10.75	9.750	XS	0.5	8.50	4	4.5	3.826	80	0.337	7.25	101.0
KRTXH10X5	10	10.75	9.750	XS	0.5	8.50	5	5.56	4.810	80	0.375	7.5	103.0
KRTXH10X6	10	10.75	9.750	XS	0.5	8.50	6	6.62	5.756	80	0.432	7.62	104.0
KRTXH10X8	10	10.75	9.750	XS	0.5	8.50	8	8.62	7.620	80	0.5	8	124.0
KRTXH12X4	12	12.75	11.750	XS	0.5	10.00	4	4.5	3.826	80	0.337	8.5	148.0
KRTXH12X5	12	12.75	11.750	XS	0.5	10.00	5	5.56	4.810	80	0.375	8.5	149.0
KRTXH12X6	12	12.75	11.750	XS	0.5	10.00	6	6.62	5.756	80	0.432	8.62	151.0
KRTXH12X8	12	12.75	11.750	XS	0.5	10.00	8	8.62	7.620	80	0.5	9	156.0
KRTXH12X10	12	12.75	11.750	XS	0.5	10.00	10	10.75	9.750	XS	0.5	9.5	165.0

*** Dimensions conform to ASME B16.9 & material conforms to ASTM SA-234 Grade B**

Pipe Fittings Direct
 690 Craig Rd
 Edgerton, WI 53534
 Phone: (608) 371-9313
 Email: sales@pipefittingsdirect.com